# Gazpromneft Cleanfluid

**Gazpromneft Cleanfluid** - biocide-free, high performance cleaner for cooling systems, production machines, circulation systems and other equipment**. Gazpromneft Cleanfluid** is recommended for cleaning the cutting fluid system of a machine tool before changing the emulsion or for stabilizing the emulsion in use, in order to extend its service life. **Gazpromneft Cleanfluid** breaks down biofilms that may accumulate in the machine tool system thereby cleaning it.

## Application

When replacing the cutting fluid, depending on the degree of contamination, it is recommended to add **Gazpromneft Cleanfluid** in an amount of 1 - 4% and work with this emulsion for 3-5 days. Metal working can continue during this period. Keep an intensive check on the filters, channels of the machine and the level in the tank, in order to destroy deposits and biofilms.

| Properties | Method | Gazpromneft Cleanfluid |
|---|---|---|
| Appearance | Visually | Homogeneous transparent liquid |
| Density at 20°C, kg/m³ | GOST 3900 | 1075 |
| pH in 5% water emulsion | GOST 6243 clause 4 | 9,9 |

**The company's management system is certified in accordance with the international standards**

ISO 9001 ISO 14001 ISO 45001

GAZPROMNEFT – LUBRICANTS, LTD.
14/3, Krzhyzhanovskogo Street, Moscow, 117218 Russia
Tel: +7 (495) 642-99-69
Fax: +7 (495) 921-48-63

The above data are typical for the products currently available. Due to ongoing research and development, the information contained in the document is subject to change. Information on the safe use of the product is contained in the Safety Data Sheet. More detailed information can be obtained from the company's technical specialists. E-mail: Techservice@gazprom-neft.ru.
06/2024